



The **AmpliVox Gooseneck-tube Microphone** is attractive and elegant, making it the ideal choice for boardrooms and conference rooms.

The easily flush mounted shockmount holder allows for steady and accurate microphone positioning.

THIS MICROPHONE CAN NOT BE USED WITH ANY 48v PHANTOM POWER SUPPLIES.

This microphone is designed to be used with AmpliVox Amplifiers.

FEATURES:

- Contemporary Design
- Unidirectional pick-up pattern—reduces background noise
- Flex-tube Design—lets you adjust its angle and height to suit your needs without sagging.
- Includes slip-on Acoustic Foam Windscreen for added protection against breath and wind noise.
- Smooth, tailored frequency response.
- Shock mount - requires 2 inch diameter cutout.
Hardware included.

MICROPHONE SPECIFICATIONS:

- Element: Electret Condenser
- Polar Pattern: Unidirectional
- Frequency Response: 50Hz - 16Khz
- Sensitivity: -35dB ±3dB
(0dB=1v/pa at 1KHz)
- Output Impedance: 300Ω ±30%
- Power Supply: DC 3V
- Product Weight: 3.7 oz. (107g)
- Product Color: Black
- Accessories: Windscreen
- Connector: XLR
- Dims: 22 inches long (558 mm)

	MODEL	MSRP
Gooseneck Microphone Kit	S2050	\$315.00