

A Complete Audio System Built Into a Stylish Adjustable Lectern

Covers Audiences up to 1,500. Adjusts from 39 to 45 inches!



Lectern easily adjusts from 39-in. to 45-in.

Color choices:

 Light oak,

 Walnut,

 Medium oak,

 Mahogany.

High pressure laminate with scratch-resistant finish.



Quick Look:

Wired, Wireless, Non-Sound
 Audience Size: 1,500
 Room Size: 15,000 sq. ft.
 SPL 106 dB
 Built-in Flush Mount Amp
 2 Jensen Speakers
 Dynamic Hot Gooseneck Mic
 Storage Space
 High Pressure Laminate
 Made in USA
 6 Year Warranty

UPGRADE YOUR LECTERN - INCREASE YOUR SOUND COVERAGE

Increase audience coverage by adding our **Dual Module Companion Speaker (S1201)** - It can be placed inside the lectern or mounted remotely on an optional tripod (S1090) giving you a **total of 4 speakers.** All items sold separately.



Features / Specifications

- ✓ Adjust the height with our smooth, effortless pneumatic dial. The reading table height can be set between 39-in. and 45-in. (measured from front of lectern)
- ✓ Exclusive built-in flush mount **Amplivox 50 watt multimedia stereo amplifier.** Battery powered or AC.
- ✓ Sculpted radius base with four hidden casters, 2 locking.
- ✓ Auxiliary input stereo jack with separate volume and tone controls for a CD player, tape player or LCD computer projector.
- ✓ Line out jack for a tape recorder. You can record your presentation as it is happening.
- ✓ 3 mic inputs (dynamic, condenser with phantom power, WIRELESS) can be used at the same time.
- ✓ 2 speaker jacks for a total of 4 speakers possible (using a Y-connector).
- ✓ **Dual Wireless Capability** - SW wireless series **SW805A Amplifier** with built-in wireless receiver allows 2 people to be wireless simultaneously with second wireless mic kit.
- ✓ On-off switch with LED power indicator light. 1 jack for optional external AC Adapter/Recharger.
- ✓ Dimensions: 15-in. D x 21-in. W x 45-in. H Weight: 85 lbs.
- ✓ Runs on 10 D-cell alkaline batteries for up to 200 hours of talk time, S1460 International AC Adapter/Recharger (110/240V; 50/60Hz), S1465 NiCad Rechargeable Battery Pack (requires S1460). All Sold Separately.
- ✓ Front Panel Dimensions for Company Engravings/logos: 22-1/4"W x 7-3/4"H

	Model #	Shpg. Wt.	MSRP
EXECUTIVE ADJUSTABLE SOUND COLUMN LECTERN Includes 50 Watt Amp, 2 built-in speakers, dynamic gooseneck mic, reading table 20 3/4-in. W x 16 1/2-in. D	S505A	85 lbs.	1,417.00
EXECUTIVE ADJUSTABLE WIRELESS SOUND COLUMN LECTERN As above with built-in wireless receiver: Plus your choice of wireless lapel/headset mic or handheld mic and transmitter, reading table 20 3/4-in. W x 16 1/2-in. D	SW505A	85 lbs.	1,710.00
NON-SOUND EXECUTIVE ADJUSTABLE SOUND COLUMN LECTERN reading table 20 3/4-in. W x 16 1/2-in. D	W505A	75 lbs.	601.00
DUAL MODULE COMPANION SPEAKER - Two 6-in. x 8-in. speakers, 40 ft. cable, (14-in.x10-in.x 6 1/2-in.)	S1201	15 lbs.	240.00
READING LAMP - Clip-on, AC, 25 watt bulb, 8-ft. cord	S1100	1 lbs.	64.00
CLIP ON GIG LIGHT - Battery powered clip on Halogen light. Requires 4 AA batteries not included.	S1135	2 lbs.	72.00
COMPACT TRIPOD 1-3/8-IN - Adjustable, 28-in. to 49-in., 27-in. folded	S1090	4 lbs.	119.00
LECTERN PROTECTIVE COVER - Brown vinyl. Water resistant. Fits 45-in.H x 27-1/2-in.W x 25-in.D.	S1972	7 lbs.	124.00

AMPLIFIER POWER SOURCE NOT INCLUDED: Powered by 10 D-cell alkaline batteries for up to 200 hours talk time; S1460 International AC Adapter/ Recharger; S1465 Rechargeable NiCad Battery Pack for up to 20 hours before recharging (requires S1460). All sold separately.

INTERNATIONAL AC ADAPTER/RECHARGER - 110/240 volt, 50/60Hz. 15-volt center positive, 2 amps, 7.5-ft cord. For S1460 S805A/SW805A amplifiers only. **S1460** **2 lbs.** **125.00**

NICAD BATTERY PACK - Heavy duty rechargeable; for S805A/SW805A amps - requires S1460 AC Adapter/Recharger. **S1465** **4 lbs.** **190.00**