



**SPECIFICATIONS**

Every Amplivox SLA battery uses maintenance-free **Valve Regulated Lead Acid (VRLA)** construction with the best materials available including the latest **Absorbed Glass Mat (AGM)** technology giving you increased durability, superior performance, longer run times between charges and longer overall battery life.

- **Voltage:** 12 V
- **Amp Hours / Watt Hours:** 7 Ah / 84 Wh
- **Charging Time:** 20 Hours full charge
- **Operating Capacity:** Fully charged batteries will provide 10 hours of typical operation, defined as speaking 35% of the time at mid volume.
- **Cycle Life:** Battery can be expected to provide 80% of its rated capacity after 400 charge / discharge cycles and 60% after 800 cycles. Storing, transporting or using the battery pack at temperatures exceeding 104° F / 40°C or 32° F / 0° C will substantially reduce the cycle life of the battery pack
- **Weight:** 5.86 lbs. (2.66 kg) per battery
- **Dimensions (HWD):** 3 3/4" H x 6" W x 2 1/2" D  
(94mm x 151mm x 65mm)
- **Warranty:** 1 Year
- UL and CE Approved

**WHY USE RECHARGEABLE BATTERIES?**

**Save Money**—While rechargeable batteries cost more initially, they can be reused hundreds of times and last for years.

**Protect the Environment—Conserve Resources**

The corrosive materials and heavy metals in batteries can impair human health and the environment. Rechargeable batteries use greatly reduces the quantity of batteries manufactured, used and discarded.

**AmpliVox** recommends recycling batteries through Call2Recycle, Inc., a 501(c)4 non-profit organization - [www.call2recycle.org](http://www.call2recycle.org)



	MODEL	Ship Weight	MSRP
Rechargeable SLA Batteries (2 batteries) .....	S1490	12 lbs	\$119.00