



SPECIFICATIONS

Every Amplivox SLA battery uses maintenance-free **Valve Regulated Lead Acid (VRLA)** construction with the best materials available including the latest **Absorbed Glass Mat (AGM)** technology giving you increased durability, superior performance, longer run times between charges and longer overall battery life.

- **Voltage:** 12 V
- **Amp Hours / Watt Hours:** 2.9 Ah / 34.8 Wh
- **Charging Time:** 20 Hours full charge
- **Terminal Type:** T1
- **Operating Capacity:** Fully charged batteries will provide 8 - 10 hours of typical operation, defined as speaking 35% of the time at mid volume.
- **Cycle Life:** Battery can be expected to provide 80% of its rated capacity after 400 charge / discharge cycles and 60% after 800 cycles. Storing, transporting or using the battery pack at temperatures exceeding 104° F / 40°C or 32° F / 0° C will substantially reduce the cycle life of the battery pack
- **Weight:** 2.4 lbs. (1.1 kg) per battery
- **Dimensions (HWD):** 3 7/8" H x 2 1/4" W x 3 1/8" D
(99mm x 56mm x 79mm)
- **Warranty:** 1 Year

WHY USE RECHARGEABLE BATTERIES?

Save Money—While rechargeable batteries cost more initially, they can be reused hundreds of times and last for years.

Protect the Environment—Conserve Resources

The corrosive materials and heavy metals in batteries can impair human health and the environment. Rechargeable batteries use greatly reduces the quantity of batteries manufactured, used and discarded.

Amplivox recommends recycling batteries through Call2Recycle, Inc., a 501(c)4 non-profit organization - www.call2recycle.org



	MODEL	Ship Weight	MSRP
Rechargeable SLA Batteries (1 battery)	S1493	6 lbs	\$107.00